

FORM PTO-1390 (REV. 12-2001)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER ESI 10199	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (If known, see 37 CFR 1.5)	
				10/069735	
INTERNATIONAL APPLICATION NO. PCT/US00/25657		INTERNATIONAL FILING DATE September 19, 2000		PRIORITY DATE CLAIMED September 20, 1999	
TITLE OF INVENTION Permanent Magnet Rotor Portion For Electric Machines					
APPLICANT(S) FOR DO/EO/US Costin Ifrim					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<p>1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.</p> <p>2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.</p> <p>3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.</p> <p>4. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31).</p> <p>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> has been communicated by the International Bureau.</p> <p style="margin-left: 20px;">c. <input checked="" type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</p> <p>6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> is attached hereto.</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4).</p> <p>7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> have been communicated by the International Bureau.</p> <p style="margin-left: 20px;">c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</p> <p style="margin-left: 20px;">d. <input type="checkbox"/> have not been made and will not be made.</p> <p>8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).</p> <p>9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</p> <p>10. <input type="checkbox"/> An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</p> <p>Items 11 to 20 below concern document(s) or information included:</p> <p>11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</p> <p>12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</p> <p>13. <input type="checkbox"/> A FIRST preliminary amendment.</p> <p>14. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</p> <p>15. <input type="checkbox"/> A substitute specification.</p> <p>16. <input type="checkbox"/> A change of power of attorney and/or address letter.</p> <p>17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.</p> <p>18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4).</p> <p>19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).</p> <p>20. <input type="checkbox"/> Other items or information:</p>					

U.S. APPLICATION NO. 10/069735		INTERNATIONAL APPLICATION NO. PCT/US00/25657		ATTORNEY'S DOCKET NUMBER ESI 10199	
---------------------------------------	--	--	--	---------------------------------------	--

21. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO. \$1040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS PTO USE ONLY <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; text-align: right;">\$100.00</td> <td style="width: 50%;"></td> </tr> </table>		\$100.00	
\$100.00							

Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
--	--	--	--	----	--

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total claims	17 - 20 =	0	x \$18.00	\$ 0.00	
Independent claims	4 - 3 =	1	x \$84.00	\$ 84.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$280.00	\$
TOTAL OF ABOVE CALCULATIONS =				\$ 184.00	
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				+	\$ 92.00
SUBTOTAL =				\$ 92.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	0.00
TOTAL NATIONAL FEE =				\$ 92.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$	40.00
TOTAL FEES ENCLOSED =				\$ 132.00	
				Amount to be refunded:	\$
				charged:	\$

a. ☒ A check in the amount of \$ 132.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☐ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. _____. A duplicate copy of this sheet is enclosed.


d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Law Offices of Raymond A. Nuzzo
 579 Thompson Avenue
 East Haven, CT 06512

Tel: 203-467-7895


 SIGNATURE
 Raymond A. Nuzzo
 NAME
 37,199
 REGISTRATION NUMBER

Rec'd PCT/PTO 25 FEB 2002

DESCRIPTIONPERMANENT MAGNET ROTOR
PORTION FOR ELECTRIC MACHINESTechnical Field

The present invention generally relates to alternators of the type that are used in vehicles to provide electrical power for running accessories and charging batteries. More particularly, this invention relates to an improved permanent magnet rotor portion for use by the alternators and other electric machines.

Background Art

Typical rotor configurations that are used in alternators are disclosed in U.S. Patent Nos. 5,693,995, 5,710,471, 5,747,909 and 5,753,989.

Disclosure of the Invention

In one aspect, the present invention is directed to a rotor for an electric machine comprising a plurality of independent poles and permanent magnets circumferentially arranged in an alternating configuration such that each permanent magnet is positioned intermediate a pair of consecutive or successive independent poles. The arrangement of the permanent magnets and independent poles defines an outer rotor perimeter and a central opening for receiving a shaft upon which the rotor rotates. Each independent pole has a generally triangular cross-section that defines an apex portion that confronts the central opening and an end portion that forms a portion of the outer rotor perimeter. Each permanent magnet has a first end for confronting the

central opening, and a second end that forms a portion of the outer rotor perimeter. Each permanent magnet tapers from the first end to the second end. This particular geometry of each permanent magnet is referred to herein as "reverse trapezoidal". An important feature of the rotor of the present invention is that the centrifugal force produced by rotation of the rotor radially pushes each permanent magnet away from the central opening. Furthermore, the aforementioned centrifugal force cooperates with the shape of the independent poles and permanent magnets to further improve the integrity of the lodgment of each permanent magnet between the corresponding pair of consecutive independent poles. Each pair of consecutive independent poles are separated by a space that has a shape that conforms to the shape of a corresponding permanent magnet that is positioned within the space.

The rotor of the present invention further comprises a pair of hubs. The permanent magnets and independent poles are positioned between the hubs. The independent poles are attached to the hubs in such a manner that there is no interconnection between the apex portions of the independent poles so as to induce magnetization having a direction that is substantially orthogonal to the radius of the rotor.

The permanent magnets are formed from a magnetic material chosen from ferrite, neodymium, ceramic and samarium-cobalt.

In a related aspect, the present invention is directed to rotor for an electric machine, comprising at least two independent poles and at least two permanent magnets arranged in an alternating configuration such that each permanent magnet is positioned intermediate a pair of consecutive or successive independent poles. The arrangement of the permanent magnets and independent poles defines an outer rotor

perimeter and a central opening for receiving a shaft upon which the rotor rotates. Each independent pole has a first end portion that confronts the central opening and a second end portion that forms a portion of the outer rotor perimeter. The second end portion of each independent pole has a pair of lips that conform to the locally defined curvature of the outer rotor perimeter. Each permanent magnet has a first end for confronting the central opening and a second end that forms a portion of the outer rotor perimeter. Each lip of the second end portion of each independent pole abuts a portion of the second end of a corresponding permanent magnet, whereby the centrifugal force produced by rotation of the rotor radially pushes each permanent magnet away from the central opening and whereby the centrifugal force cooperates with the independent poles and permanent magnets to further improve the integrity of the lodgment of each permanent magnet between the corresponding pair of independent poles. Each pair of consecutive or successive independent poles are separated by a space that has a shape that conforms to the shape of a corresponding permanent magnet that is positioned within the space. In one embodiment, each permanent magnet has a reverse trapezoidal cross-section. In another embodiment, each permanent magnet has a generally rectangular cross-section.

Brief Description of the Drawings

The features of the invention are believed to be novel. The figures are for illustration purposes only and are not drawn to scale. The invention itself, however, both as to organization and method of operation, may best be understood by reference to the detailed description which follows taken in conjunction with the accompanying

drawings in which:

FIG. 1 is an exploded view of a prior art permanent magnet rotor section.

FIG. 2 is a top plan view of the poles depicted in FIG. 1.

FIG. 3 is an exploded view of the permanent magnet rotor portion of the present invention.

FIG. 4 is a side elevational view of a permanent magnet depicted in FIG. 3.

FIG. 5 is a view taken along line 5-5 of FIG. 4.

FIG. 6 is a view taken along line 6-6 of FIG. 4.

FIG. 7 is a perspective view of the permanent magnet of FIG. 4.

FIG. 8 is a perspective view of the permanent magnet rotor section of the present invention.

FIG. 9 shows a portion of the permanent magnet rotor section shown in FIG. 8 and the flux path through that portion of the rotor.

FIG. 9A is a top plan view of a pole depicted in FIGS. 3, 8 and 9.

FIG. 10 is a diagram that illustrates properties of a focused flux path resulting from the structure of the permanent magnet rotor section of the present invention.

Modes For Carrying Out The Invention

In describing the preferred embodiments of the present invention, reference will be made herein to Figs. 1-10 of the drawings in which like numerals refer to like features of the invention.

In order to facilitate understanding and appreciation of the advantages of the permanent magnet rotor portion of the present invention, a typical prior art permanent

magnet rotor section is first described with reference being made to Figs. 1 and 2.

Referring to Figs. 1, there is shown prior art rotor assembly 10. Assembly 10 generally comprises hub 12, screws 13, hub 14 and pole structure 16. Screws 13 are disposed through corresponding openings in pole structure 16 and threadedly engaged with threaded holes 17 in hub 14.

When installed in an electric machine, rotor 10 rotates with respect to a stator (not shown). Typical configurations applied for alternators are described in commonly owned U.S. Patent Nos. 5,693,995, 5,710,471, 5,747,909 and 5,753,989, the disclosures of which are incorporated herein by reference.

Referring to Fig. 2, ten (10) rotor field poles 18 radially extend from rotor core 20. Rotor 16 is fabricated from material having a high magnetic permeability. Rotor 16 can be constructed as a single solid piece or from a plurality of laminations having a cross-sectional shape shown in Fig. 2. Spaces 22 between poles 18 are sized for receiving permanent magnets (not shown) having tangential magnetization. A mechanical clearance is required in between the dimensions of spaces 22 and the magnet dimensions in order to insert the magnets during manufacturing. As a result of such a configuration, a "parasitic" (mechanical) air gap is created which degrades the performance of the electric machine. Furthermore, an unusable flux path or flux leakage path is developed at core 20. This unusable flux path results in a significant "leakage flux" that degrades the efficiency and performance of the electric machine. These disadvantages of the prior art permanent magnet rotor section are addressed and eliminated by the permanent magnet rotor portion of the present invention.

Referring to Fig. 3, there is shown an exploded view of permanent magnet rotor

portion 50 of the present invention. Rotor portion 50 generally comprises hubs 52 and 54, permanent magnets 56, independent poles 58, holding bolts 60 and 62. Each pole 58 further includes axially extending openings 63 sized for receiving a corresponding bolt 60. Hubs 52 and 54 have threaded openings 64 for receiving bolts 62. Hubs 52 and 54 are fabricated from a non-magnetic (low magnetic permeability) material. Independent poles 58 and holding bolts 60 are fabricated from high magnetic permeability material.

Referring to Figs. 3, 4-7 and 8, in a preferred embodiment, permanent magnets 56 have a particular shape and orientation that is referred to herein as "reverse trapezoidal". The space between each pair of successive or consecutive poles 58 has a shape that conforms to the shape of the corresponding permanent magnet 56 that is positioned within that space between the pair of successive or consecutive poles 58. Each magnet 56 has end 66 which has a width W1 and end 68 which has a width W2 that is less than width W1. Magnet 56 further includes a pair of sides, one of which being designated by numeral 70, the other not being shown. Referring to Fig. 8, an important feature of the present invention is the particular shape and arrangement of poles 58 and the placement of each magnet 56 in the spaces between poles 58. Referring to Figs. 9 and 9A, each pole 58 is shaped as a disc sector and has a generally triangular cross-section wherein apex 71 of each pole 58 is directed to the center of the rotor or the shaft (not shown) upon which rotor 50 will rotate. The shape of each pole 58 and the position of each pole 58 with respect to the other poles 58 provides spaces between each pair adjacent poles 58 that generally conform to the shape of a trapezoid. Each magnet 56 is inserted in a corresponding space between each pair of

consecutive or successive poles 58. Thus, end 68 of each magnet is generally on the outside diameter or circumference of the rotor 50. One important feature of the magnet and pole configuration shown in Figs. 3, 4-7 and 8 is that there is no interconnection of apices 71 of the triangular shaped poles 58 at the internal diameter level in contrast to the prior art rotor structure shown in Fig. 2. As a result of the magnet and pole configuration of the present invention, the magnetization direction, indicated by arrow 72 (see Fig. 4), is substantially orthogonal to the radius of rotor 50. In other words, the structure and arrangement of magnets 56 and poles 58 forces the flux to be focused toward the active air gap that is between the rotor and the stator (not shown). The resulting flux path is illustrated in Fig. 9 and is indicated by numeral 74.

The shapes of magnets 56 and poles 58 cooperate to prevent magnets 56 from becoming dislodged from the spaces between poles 58. During rotation of rotor 50, a centrifugal force is applied to magnets 56 and wedges and locks the diameter of rotor 50. Thus, the problems and disadvantages associated with the unusable flux path created at the interconnection of poles 18 in the prior art rotor structure shown in Fig. 2 are eliminated by the particular structure and arrangement of permanent magnets 56 and poles 58 of rotor 50 of the present invention. In this way, "parasitic" air gaps are virtually eliminated. Referring to Fig. 9A, in a preferred embodiment, each pole 58 also includes lips 75 and 76 in order to further secure magnets 56 and to eliminate outward, radial movement of each magnet 56 into the active air gap between the rotor 50 and the stator (not shown). In an alternate embodiment, an adhesive film is applied to the contact surface between each magnet 56 and adjacent poles 58.

In an alternate embodiment, rectangular magnets can be used in place of magnets 56. In such a configuration, the space between each pair of successive or consecutive independent poles is generally rectangular shaped, and the independent poles have lips (similar to lips 75 and 76) that radially constrain the rectangular shaped magnets. An adhesive film is applied to the contact surface between the rectangular magnets and poles 58.

A preferred step in the assembly process of rotor 50 is to spin rotor 50 so as to allow the centrifugal force to radially push magnets 56 prior to balancing rotor 50.

Referring to Fig. 10, there is shown a graph of Φ vs. mmf (flux vs. magnetic motor force) graph and an equivalent circuit that represents the properties of the flux path developed by the structure and arrangement of magnets 56 and poles 58. The symbols shown in the equivalent circuit have the following meanings:

R_{gap} : machine gap air reluctance;

R_{pgap} : parasitic air gap reluctance in between each magnet 56 and pole 58;

R_{lk} : leakage reluctance present at the end of the magnets;

R_{mg0} : internal magnet reluctance defined by magnet thickness;

Φ_r : internal magnetic flux, assimilated in the magnetic circuit as an ideal current source ($\Phi_r = B_r A_{mg}$ represents the product between the remanent flux density of the permanent magnet and its surface orthogonal to the magnetization direction);

Φ_m : magnetic flux produced by the magnet;

Φ_{gap} : magnetic flux in the machine air gap.

Referring to Fig. 10, each permanent magnet 56 is pushed radially by the centrifugal force and therefore, the parasitic air gap is minimized bringing the value

R_{pgap} close to zero. This is reflected in the \emptyset vs. mmf graph by moving the load line towards the flux line. As a result, the gap flux is higher. Thus, use of independent poles 58 and the prevention of the magnetic flux in finding a shortening path substantially minimizes the leakage reluctance.

Since there is no connection between the independent poles 58 at the internal diameter level, a major leakage path has been eliminated in contrast to prior art permanent magnet rotor sections. In the configuration wherein the reverse trapezoidal shaped magnets 56 are used, these magnets substantially eliminate the parasitic air-gap that is required (due to assembly tolerances) when inserting prior art rectangular magnets into the corresponding rectangular spaces. This is due to the fact that while the rotor 50 spins, the independent poles 58 are radially held in place by hubs 52 and 54 and holding bolts 60 and 62 while permanent magnets 56 are radially pushed by the centrifugal force. Thus, the parasitic air-gap is substantially eliminated.

In view of the foregoing description, it is apparent that rotor 50 is relatively less complex in construction than prior art rotor structures. Furthermore, it is to be understood that although rotor 50 has been described in terms of being used in alternators or hybrid alternators, it is to be understood that rotor 50 can be used in any electrical machine that uses permanent magnets.

The principals, preferred embodiments and modes of operation of the present invention have been described in the foregoing specification. The invention which is intended to be protected herein should not, however, be construed as limited to the particular forms disclosed, as these are to be regarded as illustrative rather than restrictive. Variations in changes may be made by those skilled in the art without

departing from the spirit of the invention. Accordingly, the foregoing detailed description should be considered exemplary in nature and not limited to the scope and spirit of the invention as set forth in the attached claims.

Thus, having described the invention, what is claimed is:

10920 96600F

CLAIMS

1. A rotor configured for use with a vehicle alternator wherein the rotor rotates within and respect to a stator of the vehicle alternator, the rotor comprising a plurality of independent poles and permanent magnets circumferentially arranged in an alternating configuration such that each permanent magnet is positioned intermediate a pair of consecutive independent poles, the arrangement of the permanent magnets and independent poles defining an outer rotor perimeter and a central opening for receiving a shaft upon which the rotor rotates, each independent pole having a generally triangular cross-section that defines an apex portion that confronts the central opening and an end portion that forms a portion of the outer rotor perimeter, each permanent magnet having a reverse trapezoidal cross-section, a first end for confronting the central opening, and a second end that forms a portion of the outer rotor perimeter, each permanent magnet tapering from the first end to the second end, whereby the centrifugal force produced by rotation of the rotor radially pushes each permanent magnet away from the central opening and whereby the centrifugal force cooperates with the shape of the independent poles and permanent magnets to further improve the integrity of the lodgment of each permanent magnet between the corresponding pair of consecutive independent poles, the rotor being configured without any annular member being attached to the rotor about the rotor perimeter for holding the permanent magnets and independent poles in place.

2. The rotor according to claim 1 further comprising a pair of hubs, the permanent magnets and independent poles being positioned between the hubs, the independent

poles being attached to the hubs in such a manner that there is no interconnection between the apex portions of the independent poles so as to induce magnetization having a direction that is substantially orthogonal to the radius of the rotor.

3. The rotor according to claim 1 wherein the end portion of each independent pole defines a pair of lips that conforms to the locally defined curvature of the outer rotor perimeter, each lip abutting a corresponding permanent magnet.

4. The rotor according to claim 1 wherein each independent pole has an axially extending bore that is generally rectangular in shape and is sized for receiving a holding bolt that has a generally rectangular cross-section, the axially extending bore preventing rotation of the independent pole about the holding bolt and radial movement of the independent pole.

5. The rotor according to claim 4 wherein the independent poles and holding bolts are fabricated from relatively high magnetic permeable materials.

6. The magnet rotor according to claim 1 wherein each magnet is formed from a magnetic material chosen from ferrite, neodymium, ceramic and samarium-cobalt.

7. The rotor according to claim 1 wherein the independent poles are separated by a space that has a shape that conforms to the shape of a corresponding permanent magnet that is positioned within the space.

8. An independent pole for use in a permanent magnet rotor having a central opening for receiving a shaft upon which the rotor rotates, an outer rotor perimeter, and at least two permanent magnets, the independent pole having a generally triangular cross-section that defines an apex portion that confronts the central opening and an end portion that forms a portion of the outer rotor perimeter.

9. The independent pole according to claim 8 wherein the end portion of each independent pole defines a pair of lips that conforms to the locally defined curvature of the outer rotor perimeter, each lip abutting a corresponding permanent magnet.

10. The independent pole according to claim 8 wherein each independent pole has an axially extending bore that is generally rectangular in shape and is sized for receiving a holding bolt that has a generally rectangular cross-section, the axially extending bore preventing rotation of the independent pole about the holding bolt and radial movement of the independent pole.

11. The independent pole according to claim 8 wherein each independent pole is fabricated from relatively high magnetic permeable materials.

12. A permanent magnet configured for placement between of a pair of consecutive independent poles of a rotor wherein each independent pole has a generally triangular cross-section and the rotor has a central opening for receiving a shaft upon which the

rotor rotates and an outer rotor perimeter, the permanent magnet having a reverse trapezoidal cross-section, a first end for confronting the central opening, and a second end that forms a portion of the outer rotor perimeter, the permanent magnet tapering from the first end to the second end.

13. The permanent magnet according to claim 12 wherein the permanent magnet is formed from a magnetic material chosen from ferrite, neodymium, ceramic and samarium-cobalt.

14. A rotor for an alternator, comprising at least two independent poles and at least two permanent magnets arranged in an alternating configuration such that each permanent magnet is positioned intermediate a pair of consecutive independent poles, the arrangement of the permanent magnets and independent poles defining an outer rotor perimeter and a central opening for receiving a shaft upon which the rotor rotates, each independent pole having a first end portion that confronts the central opening and a second end portion that forms a portion of the outer rotor perimeter, the second end portion of each independent pole having a pair of lips that conform to the locally defined curvature of the outer rotor perimeter, each permanent magnet having a first end for confronting the central opening and a second end that forms a portion of the outer rotor perimeter, each lip of the second end portion of each independent pole abutting a portion of the second end of a corresponding permanent magnet, whereby the centrifugal force produced by rotation of the rotor radially pushes each permanent magnet away from the central opening and whereby the centrifugal force cooperates

with the independent poles and permanent magnets to further improve the integrity of the lodgment of each permanent magnet between the corresponding pair of independent poles, each independent pole having an axially extending bore that is generally rectangular in shape and is sized for receiving a holding bolt that has a generally rectangular cross-section, the axially extending bore preventing rotation of the independent pole about the holding bolt and radial movement of the independent pole, the rotor being configured without a retaining member attached to the rotor about the rotor perimeter to retain the permanent magnets and independent poles in place.

15. The rotor according to claim 14 wherein each pair of consecutive independent poles are separated by a space that has a shape that conforms to the shape of a corresponding permanent magnet that is positioned within the space.

16. The rotor according to claim 14 wherein each permanent magnet has a reverse trapezoidal cross-section.

17. The rotor according to claim 14 wherein each permanent magnet has a generally rectangular cross-section.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 March 2001 (29.03.2001)

PCT

(10) International Publication Number
WO 01/22560 A1

(51) International Patent Classification⁷: **H02K 21/12**,
21/00, 1/12, 1/00, 1/18

(72) Inventor; and
(75) Inventor/Applicant (for US only): **IFRIM, Costin**
[RO/US]; 1298 Hartford Turnpike, #9I, North Haven, CT
06473 (US).

(21) International Application Number: **PCT/US00/25657**

(22) International Filing Date:
19 September 2000 (19.09.2000)

(74) Agent: **NUZZO, Raymond, A.**; Law Offices of Raymond
A. Nuzzo, 579 Thompson Avenue, East Haven, CT 06512
(US).

(25) Filing Language: **English**

(81) Designated States (national): **CN, DE, IN, JP, US.**

(26) Publication Language: **English**

Published:

— With international search report.


— Before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments.

(30) Priority Data:
60/154,718 20 September 1999 (20.09.1999) **US**

(71) Applicant (for all designated States except US): **ECOAIR
CORP.** [US/US]; Four Industrial Circle, Hamden, CT
06517-3152 (US).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



(54) Title: **PERMANENT MAGNET ROTOR PORTION FOR ELECTRIC MACHINES**



(57) Abstract: A rotor for an electric machine comprising a plurality of independent poles (58) having a triangular cross section shape and permanent magnets (56) having a trapezoidal cross section shape. The shapes of the independent poles and permanent magnets cooperate to improve the integrity of the lodgment of each permanent magnet.

WO 01/22560 A1

1/6



2/6








Fig. 3

3/6



4/6




Fig. 8




Fig. 9




Fig. 9a




Fig. 10

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	ECC 10199
	First Named Inventor	Costin Ifrim
	COMPLETE IF KNOWN	
	Application Number	PCT . . /US00/25657
	Filing Date	
	Art Unit	
Examiner Name		

As the below named inventor, I hereby declare that:

My residence, mailing address, and citizenship are as stated below next to my name.

I believe I am the original and first inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

PERMANENT MAGNET ROTOR PORTION FOR ELECTRIC MACHINES

(Title of the Invention)

the specification of which

☐ is attached hereto

OR

☒ was filed on (MM/DD/YYYY)

09/20/2000

as United States Application Number or PCT International

PCT/US00/25657

Application Number

and was amended on (MM/DD/YYYY)

08/17/2001

(if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent, inventor's or plant breeder's rights certificate(s), or any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

[Page 1 of 2]

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

DECLARATION — Utility or Design Patent Application

Direct all correspondence to: ☐ Customer Number OR ☒ Correspondence address below

Name Law Offices of Raymond A. Nuzzo, LLC

Address 579 Thompson Avenue

City East Haven

State CT

ZIP 06512

Country US

Telephone 203-467-7895

203-467-7233
Fax

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF SOLE OR FIRST INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name
(first and middle [if any]) Costin

Family Name
or Surname Ifrim

Inventor's
Signature [Signature]

Date 2/4/02

Residence: City Hamden

State CT

Country US

Citizenship Romanian

Mailing Address 826 Shepard Avenue

City Hamden

State CT

ZIP 06514

Country US

NAME OF SECOND INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name
(first and middle [if any])

Family Name
or Surname

Inventor's
Signature

Date

Residence: City

State

Country

Citizenship

Mailing Address

City

State

ZIP

Country

☐ Additional inventors are being named on the ____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.